Listing 11.18 Migrating a page handler to a minimal API

```
app.MapPost("/api/property/booking", (BookingInputModel model) =>     ❶
{
    var numberOfDays = (int)(model.EndDate.Value -
    ➥ model.StartDate.Value).TotalDays;
    var totalCost = numberOfDays * model.Property.DayRate *
    ➥ model.NumberOfGuests;
    return Results.Ok(new { TotalCost = totalCost });                  ❷
});
```

❶ Use the MapPost method to map a POST request to the specified route, accepting a BookingInputModel as a parameter.

❷ Use the Results.Ok method to serialize the data to JSON and return it.

Next you'll modify the client script to call this new endpoint. By default, browsers do not allow scripts to make HTTP requests to another domain in a web page. This security feature is designed to mitigate cross-site request forgery, so request verification is not needed and is, therefore, not enabled for APIs. Listing 11.19 shows the client-side code amended accordingly. It only includes the Fetch request section, and the remainder is the same as the previous example. The URL for the request is modified to reflect the template passed to the `MapPost` method, and the request verification header is removed.

Listing 11.19 The Fetch request to the minimal API

```
fetch('/api/property/booking', {                ❶
    method: 'post',
    headers: {
        "Content-type": "application/json",     ❷
    },
    body: JSON.stringify(data)
```

❶ Change the URL to point to the one specified in the API registration.

❷ No need to include the request verification token