application, so you need to narrow down the applicable scope for the CSS rule. You could add a CSS class to the h5 elements and then use that to target the headings selectively:

```
h5.clickable{
    cursor: pointer;
}
```

Add this to the global stylesheet, and you are in business. Obviously, you have to remember the purpose of the clickable class, and you have to remember to apply it to all h5 elements on the page. It may be that you want to modify the style on different pages. You can do this by adding further CSS classes to act as filters. Alternatively, you can use the sections featured in Razor to include a page-specific stylesheet:

```
@section styles{
<link href="/css/city.css" rel="stylesheet">
}
```

The downside to this approach is that you increase the number of HTTP requests for the site, especially if you add page-specific stylesheets for multiple pages. You can't really use bundling to combine all these page-specific stylesheets because that defeats the object of the exercise.

CSS isolation in Razor Pages facilitates page-specific stylesheets that do not rely on sections and are bundled into one single file. The feature is enabled by default in Razor Pages, so there is no need to add additional packages or configure any services or middleware. All you have to do is place a stylesheet alongside the page it is intended to affect. You just need to follow a specific naming convention: the Razor page filename with *.css* on the end.

Taking the example above, add a file named City.cshtml.css to the Pages folder, and in it, place the style declaration to affect clickable h5 elements: