So how does it work? Well, if you look at the rendered source for the City page, you can see that an additional attribute (`b-jbmzjjkv6t`) has been injected into every HTML element in the City.cshtml template (figure 11.7).

```
34              </div>
35          </nav>
36      </header>
37      <div b-wjjjhz4rtp class="container">
38          <main b-wjjjhz4rtp role="main" class="pb-3">
39
40  <h3 b-jbmzjjkv6t>Amsterdam</h3>
41      <div b-jbmzjjkv6t class="mb-3">
42          <h5 b-jbmzjjkv6t role="button" data-id="10"
43          data-bs-toggle="modal"
44          data-bs-target="#property-modal">
45              Dam Hotel
```

Figure 11.7 An additional attribute (`b-jbmzjjkv6t`) is injected into each HTML element in the City page.

This attribute, the *scope identifier*, uniquely identifies elements within City.cshtml. Notice that the `main` and `div` elements with the `container` CSS class have different scope identifiers injected. They belong to the _Layout.cshtml file. Each Razor file that has an accompanying isolated stylesheet gets its identifier.

At build time, all the isolated stylesheets are combined into one, and their style declarations are altered, so they only apply to elements with the identifier associated with the page they target. Here’s a snippet that shows the first few lines of the generated stylesheet for my example, which includes the City.cshtml.css file content along with the _Layout.cshtml.css content.