Listing 11.24 Combining all isolated stylesheets into one at build time

```
/* _content/CityBreaks/Pages/City.cshtml.rz.scp.css */                ❶
h5[b-jbmzjjkv6t]{                                                     ❷
    cursor:pointer;
}
/* _content/CityBreaks/Pages/Shared/_Layout.cshtml.rz.scp.css */      ❶

a.navbar-brand[b-wjjjhz4rtp] {                                        ❷
  white-space: normal;
  text-align: center;
  word-break: break-all;
}
```

❶ A comment is injected that shows which page the following style applies to.

❷ The style is isolated to elements that have the specific attribute injected into them.

The scope identifier is generated by the framework, using the format `b-{10 character string},` and by default, each file gets its unique string, guaranteeing isolation of styles. You might, however, want to share styles across a small number of pages. You can achieve this by customizing the generated identifier, so multiple pages get the same value. This is done in the project file. The following example results in both the Layout and City pages sharing the same identifier: `shared-style`.

Listing 11.25 Customizing the isolation identifier for selected pages

```
<ItemGroup>
    <None Update="Pages/Shared/_Layout.cshtml.css" CssScope="shared-style" />
    <None Update="Pages/City.cshtml.css" CssScope="shared-style" />
</ItemGroup>
```

Given that CSS isolation is a build-time feature, it isn’t supported for tag helpers because they generate their output at run time.

This chapter wraps up our look at application development in Razor Pages. The final chapters concentrate more on configuring and publishing your application and ensuring it is safe against hostile activity. We’ll start in the