Listing 12.8 The custom error page including the original request URL

```
<h1>Sorry</h1>
<p>
    The page you are looking for:
    <span class="fw-bold">@Model.RequestUrl</span>
    doesn't exist on this site.
</p>
```

Table 12.1 Redirect compared to reexecute

	Redirect	Reexecute
Preserves original request URL	No	Yes
Retains HTTP status code	No	Yes
Displays custom error page content	Yes	Yes
Results in additional HTTP requests	Yes	No

Table 12.1 recaps the differences between the reexecute and redirect options provided by the StatusCodePages middleware. Going by the summary provided in table 12.1, it should be clear that `WithReExecute` should be the default choice when implementing StatusCodePages middleware in a Razor Pages application. If the error occurred because the requested resource could not be found, the user can check the original URL they requested in the browser address bar. The status code is preserved, so user agents can act accordingly, updating indexes if necessary.

You now know how to use StatusCodePages middleware or the DeveloperExceptionPage middleware to control the message the user sees when client or server errors occur within the application. However, you won’t know these errors have occurred in the application when it is running live on the web server, unless a user makes the effort to inform you. Ideally, you need to be notified whenever an error has occurred, and you want that notification to include sufficient detail about the error, so you can attempt to identify the cause, locate it, and fix it, if at all possible.