The email logger implementation takes the `IEmailSender` used in chapter 9 as a dependency and will use its `SendEmailAsync` method to generate and send the email. First, create a folder for the logger code files named Logging. This is created in the root of the project. Then add a class file named EmailLogger.cs with the following code.

Listing 12.14 The `EmailLogger` implementation

```
using Microsoft.AspNetCore.Identity.UI.Services;                          ❶

namespace CityBreaks.Logging
{
    public class EmailLogger : ILogger                                    ❷
    {
        private readonly IEmailSender _emailSender;                       ❸
        public EmailLogger(IEmailSender emailSender)                      ❸
        {                                                                 ❸
            _emailSender = emailSender;                                   ❸
        }                                                                 ❸
        public IDisposable BeginScope<TState>(TState state) => null;      ❹

        public bool IsEnabled(LogLevel logLevel) =>                       ❺
        ➥ logLevel == LogLevel.Error || logLevel == LogLevel.Critical;   ❺

        public void Log<TState>(LogLevel logLevel, EventId eventId,       ❻
        ➥ TState state, Exception exception, Func<TState,                ❻
        ➥ Exception, string> formatter)                                  ❻
        {                                                                 ❻
            if (!IsEnabled(logLevel))                                     ❻
                return;                                                   ❻
            var htmlMessage = state.ToString() + "<br><br>" +             ❻
                exception?.Message + "<br><br>" +                         ❻
                exception?.StackTrace;                                    ❻
            Task.Run(() => SendLog(htmlMessage));                         ❻
        }                                                                 ❻

        private async Task SendLog(string htmlMessage)                    ❼
        {                                                                 ❼
            var subject = "Error in application";                         ❼
            var to = "test@example.com";                                  ❼
```