This should be a one-time step. Once you have granted trust to the development certificate, you should not be asked to do so again.

By default, new Razor Pages applications are configured to run over HTTPS, whether you use the Visual Studio new project wizard to create them or the `dotnet new webapp` command. You have to explicitly opt out of HTTPS configuration by passing `---no-https` to the CLI command or unchecking the Configure for HTTPS option in the Visual Studio new project wizard, although that isn't recommended. It is not even possible to opt out of HTTPS if you want to include authorization within your application when you first create it. An application configured to use HTTPS differs from a non-HTTPS application in the following three ways:

- It has HTTPS URLs configured in the launchSettings.json file for IIS Express and Kestrel.
- It includes HTTPS redirection middleware.
- It conditionally includes HSTS middleware.

The HTTPS redirection middleware is enabled by default and forces all requests to use the HTTPS protocol. If you attempt to browse the site using the configured HTTP port, the middleware constructs a new URL, using the HTTPS port, and sends that back in the location header of the response along with a 307 status code, which tells the user agent (browser) it should retain the original HTTP method. You may have noticed when running the CityBreaks application that it always ran under HTTPS. This was the result of the HTTPS redirection middleware in action. If this has escaped your notice, try it now.

Open a command prompt or terminal/Powershell window, navigate to the folder containing the CityBreaks.proj file, and execute the `dotnet run` command. The logger (Serilog, in my case) should confirm the application is running under two URLs: one HTTPS and the other HTTP. The actual port numbers may well differ from mine:

```
[08:17:56 INF] Microsoft.Hosting.Lifetime
Now listening on: https://localhost:7236
[08:17:56 INF] Microsoft.Hosting.Lifetime
Now listening on: http://localhost:5236
```

Open a browser and its developer tools (press F12 in most browsers), and ensure the Network tab is open. Then copy the HTTP URL into the browser address bar, and press