| Option | Description | Default value |
|---|---|---|
| `Cookie` | Provides access to configuring aspects of the cookie. | If a value for the cookie name is not specified, a unique value will be generated prefixed with `.AspNetCore.Antiforgery`. |
| `FormFieldName` | The name used for the hidden form field. | `__RequestVerificationToken`. |
| `HeaderName` | The name used for the request header. | `RequestVerificationToken`. |
| `SuppressXFrameOptionsHeader` | If set to `true`, the `X-Frame-Options` header will not be set. By default, it is set with the value `SAMEORIGIN`. | `'false'`. |

You can configure these options in Program.cs. The following example changes the header name from `RequestVerificationToken` to `CSRF-TOKEN`:

```
builder.Services.AddAntiforgery(o => o.HeaderName = "CSRF-TOKEN");
```

It is possible to opt out of request verification, although now that you understand the vulnerability it is designed to prevent, you may consider it unwise to do so. This can be done globally in Program.cs by adding a new `IgnoreAntiforgeryTokenAttribute` as a global filter.

**Listing 13.3 Disabling request verification globally**

```
builder.Services.AddRazorPages().AddRazorPagesOptions(o =>
{
    o.Conventions.ConfigureFilter(new IgnoreAntiforgeryTokenAttribute());
});
```

Alternatively, you can selectively disable the check on a page-by-page basis by adding the `IgnoreAntiforgeryTokenAttribute` to the relevant `PageModel` class (not a handler method).

**Listing 13.4 Disabling request verification selectively**