Next you add a login form to the Index.cshtml file to capture the username and password and store the hashed password (listing 13.10). When the form is first submitted, the user is shown a message, confirming the password was hashed and they can sign in. When the user attempts to sign in, the password they enter is validated against the value in the hidden field, and the validation result is displayed.

Listing 13.10 The login form

```
@page
@model IndexModel
@{
    ViewData["Title"] = "Home page";
}
@if (Model.Result != null)                                          ❶
{                                                                   ❶
    <div class="alert alert-@(Model.Result == "Failed" ?            ❶
     ➥ "danger" : "success") col-4">@Model.Result</div>            ❶
}                                                                   ❶
<form method="post" class="col-4">
    <input asp-for="HashedPassword" value="@Model.HashedPassword" /> ❷
    <div class="form-group">
        <label asp-for="UserName"></label>
        <input asp-for="UserName" class="form-control" />
        <span asp-validation-for="UserName"></span>
    </div>
    <div class="form-group">
        <label asp-for="Password"></label>
        <input asp-for="Password" class="form-control" />
        <span asp-validation-for="Password"></span>
    </div>
    <div class="form-group mt-3">
        <button class="btn btn-sm btn-success">Submit</button>
    </div>
</form>
```

❶ Inspect the Result property, and if its value is Success, display a message using the Bootstrap success color scheme; otherwise, use the danger color scheme.

❷ Store the hashed password here. You need to explicitly assign the value; other-wise, it will be populated from ModelState, where it is null.

The final part of the jigsaw is an `OnPost` method, where you use the `PasswordHasher` to generate a hash or to compare the submitted password to the previously generated hash. This needs to be added to the `IndexModel`.

Listing 13.11 `OnPost` method where the `PasswordHasher` is used

```
public void OnPost()
{
    if (ModelState.IsValid)
    {
        var user = new User { UserName = UserName };
```