Listing 14.8 Loading different resources based on the environment

```
<environment include="Development">
<link rel="stylesheet" href="~/lib/bootstrap/dist/css/bootstrap.min.css" />
</environment>
<environment exclude="Development">
<link href="https://cdn.jsdelivr.net/npm/bootstrap@5.0.2/dist/css/
            ➥ bootstrap.min.css"
    rel="stylesheet"
    integrity="sha384-
EVSTQN3/azprG1Anm3QDgpJLIm9Nao0Yz1ztcQTwFspd3yD65VohhpuuCOmLASjC"
    crossorigin="anonymous">
</environment>
```

You have looked at how to set the runtime environment and use it to conditionally build a pipeline, register services, and include content. There is one final place where it is useful to be able to switch between environments: when you want to work with general application configuration settings. In the next section, you will look at the primary storage location, the appSettings.json file, in more detail and understand how it is designed to work with environments too.

14.2 Application configuration

ASP.NET Core includes an API for managing configuration settings needed by the application that includes a number of providers for retrieving data in a variety of different formats. Configuration is set up as part of the `WebApplication.CreateBuilder` method called in Program.cs. Various key-value stores are added to configuration by default:

- The appSettings.json file
- User secrets (if the environment is `Development`)
- Environment variables
- Command-line arguments