of a list of cities, which is then passed to its `View` method. It also logs an informational message when the database call is completed.

Listing 14.19 The `CitiesViewComponent` class

```
using CityBreaks.Services;
using Microsoft.AspNetCore.Mvc;

namespace CityBreaks.ViewComponents
{
    public class CitiesViewComponent : ViewComponent                    ❶
    {
        private readonly ICityService _cityService;                     ❷
        private readonly ILogger<CitiesViewComponent> _logger;          ❷

        public CitiesViewComponent(ICityService cityService,            ❷
        ➥ ILogger<CitiesViewComponent> logger)                         ❷
        {                                                               ❷
            _cityService = cityService;                                 ❷
            _logger = logger;                                           ❷
        }                                                               ❷

        public async Task<IViewComponentResult> InvokeAsync()           ❸
        {                                                               ❸
            var cities = await _cityService.GetAllAsync();              ❸
            _logger.LogInformation("Cities                              ❸
            ➥ retrieved from the view component");                     ❸
            return View(cities);                                        ❸
        }                                                               ❸
    }
}
```

❶ Name the class with ViewComponent as a suffix, which derives from ViewComponent.

❷ Inject ICityService and a logger via the constructor as a dependency.

❸ Obtain a list of cities, log a message, and pass data as a model to the View method.

The next task is to produce the view part of the component. By default, the view name is `default`, and it is expected to be found at \Pages\Shared \Components\[View Component Name] \default. So you create a folder named Components in \Pages\ Shared and then add a folder to that named