Cities. Within that folder, add a new .cshtml file—not a Razor page, just an empty file with the name default.cshtml. The file content is shown in the next listing. It features an `@model` directive, and the rest of the content is lifted directly from the \Pages\Index.cshtml file.

Listing 14.20 The view for the `CitiesViewComponent`

```
@model List<City>
@foreach (var city in Model)
{
    <div class="col-4 p-3" style="text-shadow: rgb(0, 0, 0) 1px 1px 1px">
        <div class="card p-3 shadow"
         ➥ style="background:url(/images/cities/@city.Photo) no-repeat
         ➥ center center;background-size: cover;height:240px;">
            <h3>
                <a class="text-white text-decoration-none" asp-page="/City"
                 ➥ asp-route-name="@city.Name">@city.Name</a>
                <img src="/images/flags/@(city.Country.CountryCode).png"
                 ➥ aria-label="@($"{city.Name},
                 ➥ {city.Country.CountryName}")">
            </h3>
            <h6 class="text-white">@city.Properties.Count() properties</h6>
        </div>
    </div>
}
```

The view component tag helper targets the `<vc>` tag, with the name of the view component supplied using kebab-case after a colon. Next add the bold-font line in listing 14.21 to the ViewImports file, which activates the view component tag helper.

Listing 14.21 Activating the view component tag helper

```
@using CityBreaks
@using CityBreaks.Models
@namespace CityBreaks.Pages
@addTagHelper *, Microsoft.AspNetCore.Mvc.TagHelpers
@addTagHelper *, CityBreaks
```