Method	Return type	Notes
`Get`	`object`	Gets the item with the specified key.
`Get<TItem>`	`TItem`	Gets the item with the specified key and attempts to cast it to the specified type.
`GetOrCreate<TItem>`	`TItem`	If the item doesn't exist in the cache, this method will add it.
`Task<TItem> GetOrCreateAsync`	`Task<TItem>`	Async version of above.
`Set<TItem>`	`TItem`	Also has four overloads that allow various options to be set.
`TryGetValue<TItem>`	`bool`	Generic version of the interface method.

To demonstrate the `IMemoryCache`, you are going to add a new method to the `ICityService` that returns a list of strings, representing all the city names in the database. The method implementation will check the memory cache first, and if the data exists there, it will be retrieved. Otherwise, the memory cache will be populated from the database before being returned from the method. Then, after ensuring the existing `CityRouteConstraint` has been applied to the City page's route template, you will use the service within the constraint to check whether the route value passed to the `name` parameter is valid.

Begin by injecting both the `IMemoryCache` service and a logger into the `CityService` class. To do this, you need to add a using directive for `Microsoft.Extensions.Caching .Memory`. The altered fields and constructor of the `CityService` are shown in the following listing.

Listing 14.24 Modified fields and constructor of the `CityService`