assemblies. This has been introduced as an experimental feature in .NET 6 and is enabled by adding the following `handlerSettings` section to the `aspNetCore` section in the web.config file.

Listing 14.27 Enabling experimental shadow copy

```
<aspNetCore processPath=".\WebApplication1.exe" stdoutLogEnabled="false"
    stdoutLogFile=".\logs\stdout" hostingModel="inprocess">
  <handlerSettings>                                                    ❶
    <handlerSetting name="experimentalEnableShadowCopy"                ❶
     ➥ value="true" />                                                ❶
    <handlerSetting name="shadowCopyDirectory"                         ❶
     ➥ value="../ShadowCopyDirectory/" />                             ❶
  </handlerSettings>                                                   ❶
</aspNetCore>
```

❶ The handlerSettings section enables experimental shadow copying.

Note that shadow copying is experimental in .NET 6, and the recommendation remains to use the app_offline.htm file to manage this situation.

SUPPRESSING LANGUAGE FOLDERS

You may see a collection of folders named Ccs, Dde, Ees, and so on within the published output. These folders contain localized resources (translated error messages, warnings, and so on) for a variety of libraries and are not intended to be deployed with your application. They typically result from including design tool libraries within your application. You have included two in the CityBreaks application: `Microsoft.EntityFrameworkCore.Tools` and `Microsoft.VisualStudio.Web.CodeGeneration.Design`. The second of these was actually included for you by the page scaffolder. To suppress generation of the localized resources, just add