The following listing shows how to obtain the part of the day from the current time and render that to the browser.

### Listing 2.4 Adding dynamic content to the Razor page

```
@page
@model WebApplication1.Pages.WelcomeModel
@{
    ViewData["Title"] = "Welcome!";

    var partOfDay = "morning";                                          ❶
    if(DateTime.Now.Hour > 12){
        partOfDay= "afternoon";                                         ❷
    }
    if(DateTime.Now.Hour > 18){
        partOfDay= "evening";                                           ❸
    }
}
<h1>Welcome</h1>
<p>It is @partOfDay on @DateTime.Now.ToString(“dddd, dd MMMM”)</p>     ❹
```

❶ The partOfDay variable is declared and initialized with a value of "morning".

❷ If it is after midday, the variable is reassigned with a value of "afternoon".

❸ If it is after 6:00 p.m., the value is updated to "evening".

❹ The variable is rendered to the browser along with the current time of day.

The changes involve declaring a variable named `partOfDay`, which is instantiated with a value of `"morning"`. Two `if` statements subsequently change the value depending on the time of day. If it is after midday, `partOfDay` is changed to `"afternoon"`. It is changed again after 6:00 p.m. to `"evening"`. All of this is pure C# code and is placed in a code block, which starts with `@{` and ends with a closing `}`. Then you added an HTML paragraph element under the Welcome heading, including that text with two C# expressions, both prefixed with the @ sign. You have just written your first piece of Razor template syntax. The @ prefix tells Razor to render the value of the C# expressions. This time, depending on the