This application consists of a single project. As such, it doesn't actually need to be housed in a solution at all, but Visual Studio creates the solution file anyway. You created the solution file via the `dotnet new sln` command if you used the CLI to create your application. Then you added the WebApplication1 project to the solution explicitly via the `dotnet sln add` command. You could have skipped these steps, only creating a solution file if you needed to add additional projects to the application.

2.2.2 The WebApplication1.csproj file

The CSPROJ file is an XML-based file that contains information about the project for the build system, known as MSBuild, which is responsible for converting your source code files into a format that can be executed against the .NET runtime. To begin with, the project file contains information relating to the version of the .NET Framework the project targets and the SDK you are using. The Microsoft.NET.Sdk is the base SDK, which is used for, among other things, building console and class library projects. Web applications are built against the Microsoft.NET.Sdk.Web SDK.

The project file includes two additional properties: `Nullable` and `ImplicitUsings`. These enable you to toggle new C# features. The first sets the *nullable annotations and warnings context* for the project. In plain English, this controls the level of feedback you get from code analyzers that look for potential sources of the `NullReferenceException` in your code. This exception is the cause of more confusion and questions across .NET-focused technical communities than any other. The feature, known as *nullable reference types*, is enabled by default. You can switch it off by changing the value to `disable`.