port number is provided to the SSL port. These are generated on a per-project basis. You are free to change the port numbers if you like.

The second profile uses the project name to identify itself. If you select this profile to launch the application, it will run purely on its internal or in-process web server. The default server implementation is known as Kestrel. You will learn more about that later in this chapter. The final profile (WSL 2) relates to running the application within Windows Subsystem for Linux. This book doesn't covering WSL, but the Microsoft documentation provides a good starting place if you would like to learn more: https://docs.microsoft.com/en-us/windows/wsl/.

2.2.5 The wwwroot folder

The wwwroot folder is a special folder within the web application. It has a globe icon in Solution Explorer. It is the web root directory and houses static files. By virtue of being the web root directory, wwwroot is configured to allow its contents to be browsed directly. It is the correct location for stylesheets, JavaScript files, images, and other content that doesn't require any processing before it is downloaded to the browser. For this reason, you should not place any files in the wwwroot folder that you don't want users to be able to access. It is possible to configure an alternative location as the web root directory, but your new location won't get the special icon in Solution Explorer.

The project scaffolder has created three folders within the wwwroot folder: css, js, and lib. The css folder houses a site.css file, containing some basic style declarations for the template site. The js folder contains a file named site.js, which has nothing aside from some comments in it. The general idea is that you will place your own JavaScript files in this folder. The lib folder contains external style and script libraries. The libraries provided by the