```
app.MapRazorPages();
app.Run
```

❶ StaticFileMiddleware will never see requests as authenticated, even after you sign in.

❷ Adds AuthenticationMiddleware after UseRouting() and before UseAuthorization

❸ Middleware after AuthenticationMiddleware can read the user principal from HttpContext.User.

You've configured your app to use Identity, so the next step is updating EF Core's data model. You're already using EF Core in this app, so you need to update your database schema to include the tables that Identity requires.

23.4.2 Updating the EF Core data model to support Identity

The code in listing 23.3 won't compile, as it references the `ApplicationUser` type, which doesn't yet exist. Create the `ApplicationUser` in the Data folder, using the following line:

```
public class ApplicationUser : IdentityUser { }
```

It's not strictly necessary to create a custom user type in this case (for example, the default templates use the raw `IdentityUser`), but I find it's easier to add the derived type now rather than try to retrofit it later if you need to add extra properties to your user type.

In section 23.3.3 you saw that Identity provides a `DbContext` called `IdentityDbContext`, which you can inherit from. The `IdentityDbContext` base class includes the necessary `DbSet<T>` to store your user entities using EF Core.

Updating an existing `DbContext` for Identity is simple: update your app's `DbContext` to inherit from `IdentityDbContext` (which itself inherits from `DbContext`), as shown in the following listing. We're using the generic