In ASP.NET Core the rules that define whether a user is authorized are encapsulated in a *policy*.

DEFINITION A *policy* defines the requirements you must meet for a request to be authorized.

Policies can be applied to an endpoint using the `[Authorize]` attribute, similar to the way you saw in section 24.2.1. This listing shows a Razor Page `PageModel` that represents the first authorization step in the airport scenario. The AirportSecurity.cshtml Razor Page is protected by an `[Authorize]` attribute, but you've also provided a policy name, `"CanEnterSecurity"`, as shown in the following listing.

Listing 24.3 Applying an authorization policy to a Razor Page

```
[Authorize("CanEnterSecurity")]                ❶
public class AirportSecurityModel : PageModel
{
    public void OnGet()                        ❷
    {

    }
}
```

❶ Applying the "CanEnterSecurity" policy using [Authorize]

❷ Only users that satisfy the "CanEnterSecurity" policy can execute the Razor Page.

If a user attempts to execute the AirportSecurity.cshtml Razor Page, the authorization middleware verifies whether the user satisfies the policy's requirements (we'll look at the policy itself shortly). This gives one of three possible outcomes:

- *The user satisfies the policy*—The middleware pipeline continues, and the `EndpointMiddleware` executes the Razor Page as normal.