```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args);

builder.Services.AddAuthorizationBuilder()          ❶
    .AddPolicy(                                     ❷
        "CanEnterSecurity",                         ❸
        policyBuilder => policyBuilder              ❹
            .RequireClaim("BoardingPassNumber"));   ❹
});
// Additional configuration
```

❶ Calls AddAuthorizationBuilder to add the required authorization services

❷ Adds a new policy

❸ Provides a name for the policy

❹ Defines the policy requirements using AuthorizationPolicyBuilder

When you call `AddPolicy` you provide a name for the policy, which should match the value you use in your `[Authorize]` attributes, and you define the requirements of the policy. In this example, you have a single simple requirement: the user must have a claim of type `BoardingPassNumber`. If a user has this claim, whatever its value, the policy is satisfied, and the user will be authorized.

NOTE A *claim* is information about the user, as a key-value pair. A *policy* defines the requirements for successful authorization. A policy may require that a user have a given claim, or it may specify more complex requirements, as you'll see shortly.

`AuthorizationPolicyBuilder` contains several methods for creating simple policies like this, as shown in table 24.1. For example, an overload of the `RequireClaim()` method lets you specify a specific value that a claim must have. The following would let you create a policy where the `"BoardingPassNumber"` claim must have a value of `"A1234"`: