```
Token: eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1bmlxdWVfbmFtZSI6ImFuZHJl...
```

This is handy if you're creating tokens ad hoc at the command line, but the alternative output options may be more useful for scripts. For example, running

```
dotnet user-jwts create --output token
```

outputs the token only,

```
eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1bmlxdWVfbmFtZSI6ImFuZHJl...
```

which is much more convenient if you're trying to parse the output in a script, for example. Alternatively, you can pass `--output json`, which prints details about the JWT instead, as in this example:

```
{
  "Id": "8bf9b2fd",
  "Scheme": "Bearer",
  "Name": "andrewlock",
  "Audience": " https://localhost:7236, http://localhost:5229",
  "NotBefore": "2022-10-22T17:50:26+00:00",
  "Expires": "2023-01-22T17:50:26+00:00",
  "Issued": "2022-10-22T17:50:26+00:00",
  "Token": "eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.eyJ1bmlxdWVfbmFtZSI6Im...",
  "Scopes": [],
  "Roles": [],
  "CustomClaims": {}
}
```

Note that this isn't the payload of the token; it's the configuration details used to create the `JWT`. The token itself is exposed in the `Token` field. Again, this may be useful if you're generating JWTs using a script and need to parse the output.