The following listing shows how to configure an OpenAPI document using Swashbuckle for an API that uses JWT bearer authentication. The values defined on `OpenApiSecurityScheme` match the default settings configured by the user-jwts tool when you use `AddJwtBearer()`. `AddSecurityDefinition()` defines a security scheme for your API, and `AddSecurityRequirement()` declares that the whole API is protected using the security scheme.

Listing 25.2 Adding bearer authentication to an OpenAPI document using Swashbuckle

```
WebApplicationBuilder = WebApplication.CreateBuilder(args);

builder.Services.AddAuthentication().AddJwtBearer();
builder.Services.AddAuthorization();

builder.Services.AddEndpointsApiExplorer();
builder.Services.AddSwaggerGen(x =>
{
    x.SwaggerDoc("v1", new OpenApiInfo {
        Title = "Recipe App", Version = "v1" });

    var security = new OpenApiSecurityScheme                    ❶
  {
        Name = HeaderNames.Authorization,                       ❷
        Type = SecuritySchemeType.ApiKey,                       ❸
        In = ParameterLocation.Header,                          ❹
        Description = "JWT Authorization header",               ❺
        Reference = new OpenApiReference
        {
            Id = JwtBearerDefaults.AuthenticationScheme,        ❻
            Type = ReferenceType.SecurityScheme                 ❼
        }
    };

    x.AddSecurityDefinition(security.Reference.Id, security);   ❽
    x.AddSecurityRequirement(new OpenApiSecurityRequirement     ❾
        {{security, Array.Empty<string>()}});                   ❾
});

var app = builder.Build();
```