Figure 25.11 Adding an `Authorization` header using Swagger UI. When adding the token, ensure that you enter `Bearer <token>`, including the `Bearer` prefix. Swagger UI then attaches the token to all subsequent requests, so you are authorized to call the API.

If you're specifically using OpenID Connect or OAuth 2.0 to protect your APIs, you can configure these in the `OpenApiSecurityScheme` document instead of using bearer authentication. In that case, choosing Authorize in Swagger UI would redirect you to your identity provider to sign in and retrieve a token without your having to copy and paste anything. That's extremely useful if you're running an identity provider locally or exposing Swagger UI in production.

The example in listing 25.2 shows the configuration when your whole API is protected by an authorization requirement. That's the most common situation in my experience, but you may want to expose certain endpoints to anonymous users without any authorization requirements. In that case, you can configure Swashbuckle to conditionally apply the requirement to only those endpoints with a requirement.

TIP See the Swashbuckle documentation to learn how to configure this and many other features related to OpenAPI document generation: http://mng.bz/6D1A. Swashbuckle is highly extensible, but as always, it's worth considering whether the added complexity you introduce to achieve perfect documentation of your API is worth the tradeoff. For publicly exposed OpenAPI documents, this may well be the case, but for local testing or internal APIs, the argument may be harder to make.

In this chapter we've looked in depth at using JWT bearer tokens for authentication and explored the parallels with cookie authentication for traditional apps. In the final section of this chapter we look at authorization