1. Publish your app using `dotnet publish`. If you're creating an RDD, the output is the same as you'd use with IIS. For an SCD, you must provide the runtime identifier, as described in section 27.1.1.
2. Install the necessary prerequisites on the server. For an RDD deployment, you must install the .NET 7 Runtime and the necessary prerequisites. You can find details on this in Microsoft's "Install .NET on Linux" documentation at http://mng.bz/Rxlj.
3. Copy your app to the server. You can use any mechanism you like: FTP, USB stick, or whatever you need to get your files onto the server!
4. Configure a reverse proxy, and point it to your app. As you know by now, you may want to run your app behind a reverse proxy, for the reasons described in section 27.1. In Windows you'd use IIS, but in Linux you have more options. NGINX, Apache, and HAProxy are commonly used options. The ASP.NET Core-based YARP is also an option (https://microsoft.github.io/reverse-proxy). Alternatively, go without, and expose your app directly to the network.
5. Configure a process-management tool for your app. In Windows, IIS acts as both a reverse proxy and a process manager, restarting your app if it crashes or stops responding. In Linux, you typically need to configure a separate process manager to handle these duties; the reverse proxies won't do them for you.

The first three steps are generally the same, whether you're running in Windows with IIS or in Linux, but the last two steps are more interesting. By