chapter 30), you can add the middleware to the start of your middleware pipeline manually, as shown in listing 27.1, and configure it with the headers to look for.

WARNING It's important that `ForwardedHeadersMiddleware` be placed early in the middleware pipeline to correct `Request.Scheme` before any middleware that depends on the scheme runs.

Listing 27.1 Configuring an app to use forwarded headers in Startup.cs

```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args);
WebApplication app = builder.Build();

app.UseForwardedHeaders(new ForwardedHeadersOptions          ❶
{
    ForwardedHeaders = ForwardedHeaders.XForwardedFor |      ❷
                       ForwardedHeaders.XForwardedProto      ❷
});
app.UseHttpsRedirection();                                   ❸
app.UseRouting();                                            ❸
app.MapGet("/", () => "Hello world!");
app.Run();
```

❶ Adds ForwardedHeadersMiddleware early in your pipeline

❷ Configures the headers the middleware should look for and use

❸ The forwarded headers middleware must be placed before all other middleware.

NOTE This behavior isn't specific to reverse proxies on Linux; the `UseIis()` extension adds `ForwardedHeadersMiddleware` under the hood as part of its configuration when your app is running behind IIS.

Aside from considering the forwarded headers, you need to consider a few minor things when deploying your app to Linux that may trip you up if you're used to deploying to Windows alone: