TIP You may need to close your browser after trusting the certificate to clear the browser's cache.

If you're using Windows, Visual Studio, and IIS Express for development, then you might not need to explicitly trust the development certificate. IIS Express acts as a reverse proxy when you're developing locally, so it handles the SSL/TLS setup itself. On top of that, Visual Studio should trust the IIS development certificate as part of installation, so you may never see the browser warnings at all.

TIP In macOS, before .NET 7, you would have to retrust the developer certificate repeatedly for every new app. In .NET 7, the process is a lot smoother, so you shouldn't have to retrust it anything like as often!

Trusting the developer certificate works smoothly in Windows and macOS, in most cases. Unfortunately, trusting the certificate in Linux is a little trickier and depends on the specific flavor of Linux you're using. On top of that, software in Linux often uses its own certificate store, so you'll probably need to add the certificate directly to your favorite browser. If you're using any of the following scenarios, you'll need to do more work:

- Firefox browser in Windows, macOS, or Linux
- Edge or Chrome browsers in Linux
- API-to-API communication in Linux
- An app running in Windows Subsystem for Linux (WSL)
- Running applications in Docker

Each of these scenarios requires a slightly different approach. In many cases it's one or two commands, so I suggest following the documentation for your scenario carefully at http://mng.bz/JglK.