- After your services are configured you call `Build()` on the `WebApplicationBuilder` instance to create a `WebApplication` instance. You use `WebApplication` to configure your app's middleware pipeline, to register the endpoints, and to start the server listening for requests.
- Middleware defines how your application responds to requests. The order in which middleware is registered defines the final order of the middleware pipeline for the application.
- The `WebApplication` instance automatically adds `RoutingMiddleware` to the start of the middleware pipeline and `EndpointMiddleware` as the last middleware in the pipeline.
- Endpoints define how a response should be generated for a given request and are typically tied to a request's path. With minimal APIs, a simple function is used to generate a response.
- You can start the web server and begin accepting HTTP requests by calling `Run` on the `WebApplication` instance.

---

1. If you want to learn more about Kestrel, IIS HTTP Server, and HTTP.sys, this documentation describes the differences among them: http://mng.bz/6DgD.
2. You can install the development certificate in Windows and macOS. For instructions on trusting the certificate on Linux, see your distribution's instructions. Not all browsers (Mozilla Firefox, for example) use the certificate store, so follow your browser's guidelines for trusting the certificate. If you still have difficulties, see the troubleshooting tips at http://mng.bz/o1pr.
3. You can read about the new C# features included in .NET 7 and C# 11 at http://mng.bz/nWMg.
4. You can read in more detail about HTTP logging in the documentation at http://mng.bz/QPmw.