- Has a `MaxAge` of at least one year, though two years are recommended
- Has the `includeSubDomains` directive
- Has the `preload` directive

Listing 28.3 shows how you can configure these directives in your app. The listing also shows how to exclude the domain never-https.com so that if you host your app at this domain, HSTS headers won't be sent. This can be useful for testing purposes.

Listing 28.3 Configuring the application HSTS header for preload

```
builder.Services.AddHsts(options =>
{
    options.Preload = true;                              ❶
    options.IncludeSubDomains = true;                    ❷
    options.MaxAge = TimeSpan.FromDays(365);             ❸
    options.ExcludedHosts.Add("never-https.com");        ❹
});
```

❶ Sends the preload directive

❷ Sends the includeSubDomains directive

❸ You must use a max-age directive of at least one year.

❹ Don't send the HSTS header in responses to requests for this domain.

Once you've prepared your application for HSTS preload, you can submit your app for inclusion in the HSTS preload list that ships with modern browsers. Visit the site https://hstspreload.org, confirm that your application meets the requirements, and submit your domain. If all goes well, your domain will be included in a future release of all modern browsers!

TIP For more details on HSTS and attacks it can mitigate, see Scott Helme's article "HSTS—The missing link in Transport Layer Security," at http://mng.bz/5wwa.