NOTE Even with HSTS and the HTTPS redirection middleware, there is still an inherent weakness: by default, browsers always make an initial insecure request over HTTP to your app. The only way to prevent this is with HSTS preload, which tells browsers to always use HTTPS.

The `HttpsRedirectionMiddleware` is added in some of the default ASP.NET Core templates. It is typically placed after the error handling and `HstsMiddleware`, as shown in the following listing. By default, the middleware redirects all HTTP requests to the secure endpoint, using an HTTP `307 Temporary Redirect` status code.

Listing 28.4 Using `HttpsRedirectionMiddleware`

```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args);

builder.Services.AddRazorPages();
builder.Services.AddHsts(o => options.MaxAge = TimeSpan.FromHours(1));

WebApplication app = builder.Build();

if(app.Environment.IsProduction())
{
    app.UseHsts();
}

app.UseHttpsRedirection();    ❶

app.UseStaticFiles();
app.UseRouting();

app.MapRazorPages();

app.Run();
```

❶ Adds the HttpsRedirectionMiddleware to the pipeline and redirects all HTTP requests to HTTPS

The `HttpsRedirectionMiddleware` automatically redirects HTTP requests to the first configured HTTPS endpoint for your application. If your application isn't configured for HTTPS, the middleware *won't* redirect and instead logs a warning: