- You can configure an HTTPS certificate for Kestrel in production using the `Kestrel:Certificates:Default` configuration section. This does not require any code changes to your application; Kestrel automatically loads the certificate when your app starts and uses it to serve HTTPS requests.
- You can use the `HstsMiddleware` to set HSTS headers for your application to ensure that the browser always sends HTTPS requests to your app instead of HTTP requests. HSTS can be enforced only when an initial HTTPS request is made to your app, so it's best used in conjunction with HTTP to HTTPS redirection.
- You can enable HSTS preload for your application to ensure that HTTP requests from browsers are never sent and are always upgraded to HTTPS. You must configure your app as shown in listing 28.3, deploy your app with a TLS certificate, and register your app at the URL https://hstspreload.org. This will schedule your app to be included in browsers' built-in list of HTTPS only sites.
- You can enforce HTTPS for your whole app using the `HttpsRedirectionMiddleware`. This will redirect any HTTP requests to the HTTPS version of endpoints.
- If you're building an API application, you should avoid exposing your application over HTTP entirely and use only HTTPS. Mobile and other nonbrowser clients don't have protections such as HSTS, so there's no safe way to support both HTTP and HTTPS. Disable HTTP for your app by listening only on https:// URLs, such as by setting `ASPNETCORE_URLS=https://*:5001`.