```
    })                                                              ❺
    .UseDefaultServiceProvider((context, options) =>                ❻
    {                                                               ❻
        var isDevelopment = context.HostingEnvironment              ❻
                                   .IsDevelopment();                ❻
        options.ValidateScopes = isDevelopment;                     ❻
        options.ValidateOnBuild = isDevelopment;                    ❻
    });                                                             ❻

  return builder;                                                   ❼
}
```

❶ Creates an instance of HostBuilder

❷ The content root defines the directory where configuration files can be found.

❸ Configures hosting settings such as determining the hosting environment

❹ Configures application settings

❺ Sets up the logging infrastructure

❻ Configures the DI container, optionally enabling verification settings

❼ Returns HostBuilder for further configuration by calling extra methods before calling Build()

The first method called on `HostBuilder` is `UseContentRoot()`. This tells the application in which directory it can find any configuration or Razor files it needs later. This is typically the folder in which the application is running, hence the call to `GetCurrentDirectory`.

TIP Remember that `ContentRoot` is not where you store static files that the browser can access directly. That's the `WebRoot`, typically wwwroot.

The `ConfigureHostingConfiguration()` method is where your application determines which `HostingEnvironment` it's currently running in. The framework looks for environment variables that start with `"DOTNET_"` (such as the `DOTNET_ENVIRONMENT` variable you learned about in chapter 10) and command-line arguments to determine whether it's running in a development or production environment.