```
    });                                                    ❹
});

app.UseStaticFiles();                                      ❺
app.UseRouting();                                          ❺

app.MapRazorPages();                                       ❺
app.Run();
```

❶ Every request passes through this middleware.

❷ The Map extension method branches if a request starts with /ping.

❸ This middleware runs only for requests matching the /ping branch.

❹ The Run extension always returns a response, but only on the /ping branch.

❺ The rest of the middleware pipeline run for requests that don't match the /ping branch.

The `Map` middleware creates a completely new `IApplicationBuilder` (called `branch` in the listing), which you can customize as you would your main `app` pipeline. Middleware added to the `branch` builder are added only to the branch pipeline, not the main trunk pipeline.

TIP The `WebApplication` object you typically add middleware to implements the `IApplicationBuilder` interface. Most extension methods for adding middleware use the `IApplicationBuilder` interface, so you can use the extension methods in branches as well as your main middleware pipeline.

In this example, you add the `Run` middleware to the branch, so it executes only for requests that start with `/ping`, such as `/ping`, `/ping/go`, and `/ping?id=123`. Any requests that don't start with `/ping` are ignored by the `Map` extension. Those requests stay on the main trunk pipeline and execute the next middleware in the pipeline after `Map` (in this case, the `StaticFilesMiddleware`).