WARNING There are several `Map` extension method overloads. Some of these are extension methods on `IApplicationBuilder` and are used to branch the pipeline, as you saw in listing 31.2. Other overloads are extensions on `IEndpointRouteBuilder` and are used to create minimal endpoints, using the endpoint routing system. If you're struggling to make your app compile, make sure that you're not accidentally using the wrong `Map` overload!

If you need to, you can create sprawling branched pipelines using `Map`, where each branch is independent of every other. You could also nest calls to `Map` so you have branches coming off branches.

The `Map` extension can be useful, but if you try to get too elaborate, it can quickly get confusing. Remember that you should use middleware for implementing cross-cutting concerns or simple endpoints. The endpoint routing mechanism of minimal APIs and Razor Pages is better suited to more complex routing requirements, so always favor it over Map where possible.

One situation where `Map` can be useful is when you want to have two independent subapplications but don't want the hassle of multiple deployments. You can use `Map` to keep these pipelines separate, with separate routing and endpoints inside each branch of the pipeline.

TIP This approach can be useful, for example, if you're embedding an OpenID Connect server such as IdentityServer in your application. By mapping IdentityServer to a branch, you ensure that the endpoints and controllers in your main app can't interfere with the endpoints exposed by IdentityServer.