31.1.5 Converting middleware into endpoint routing endpoints

In this section you'll learn how you can take the custom middleware you created in section 31.1.2 and convert it to a simple middleware endpoint that integrates into the endpoint routing system. Then you can take advantage of features such as routing and authorization.

In section 31.1.2 I described creating a simple ping-pong endpoint, using the `Map` and `Run` extension methods, that returns a plain-text `pong` response whenever a `/ping` request is received by branching the middleware pipeline. This is fine because it's so simple, but what if you have more complex requirements?

Consider a basic enhancement of this ping-pong example. How would you add authorization to the request? The `AuthorizationMiddleware` looks for metadata on endpoints like Razor Pages or minimal APIs to see whether there's any authorization metadata, but it doesn't know how to work with the ping-pong `Map` extension.

Similarly, what if you wanted to use more complex routing? Maybe you want to be able to call `/ping/3` and have your ping-pong middleware reply `pong-pong-pong`. (No, I can't think why you would either!) You now have to try to parse that integer from the URL, make sure it's valid, and so on. That's sounding like a lot more work and seems to be a clear indicator you should have created a minimal API endpoint using endpoint routing!

For our simple ping-pong endpoint, that wouldn't be hard to do, but what if you have a more complex middleware component that you don't want to