that add new elements to your HTML markup, as well as Tag Helpers that can remove or customize existing markup. You'll also see that your custom Tag Helpers integrate with the tooling of your integrated development environment (IDE) to provide rich IntelliSense in the same way as the built-in Tag Helpers.

In my opinion, Tag Helpers are one of the best additions to the venerable Razor template language in ASP.NET Core. They allow you to write Razor templates that are easier to read, as they require less switching between C# and HTML, and they augment your HTML tags rather than replace them (as opposed to the HTML Helpers used extensively in the legacy version of ASP.NET).

ASP.NET Core comes with a wide variety of Tag Helpers (see chapter 18), which cover many of your day-to-day requirements, especially when it comes to building forms. For example, you can use the Input Tag Helper by adding an `asp-for` attribute to an `<input>` tag and passing a reference to a property on your `PageModel`, in this case `Input.Email`:

```
<input asp-for="Input.Email" />
```

The Tag Helper is activated by the presence of the attribute and gets a chance to augment the `<input>` tag when rendering to HTML. The Input Tag Helper uses the name of the property to set the `<input>` tag's `name` and `id` properties, the value of the model to set the `value` property, and the presence of attributes such as `[Required]` or `[EmailAddress]` to add attributes for validations:

```
<input type="email" id="Input_Email" name="Input.Email"
    value="test@example.com" data-val="true"
    data-val-email="The Email Address field is not a valid e-mail address."
    data-val-required="The Email Address field is required."
    />
```