WARNING Always HTML-encode your output before writing to your tag with `SetHtmlContent()`. Alternatively, pass unencoded input to `SetContent()`, and the output will be automatically HTML-encoded for you.

Before you can use your new Tag Helper in a Razor template, you need to register it. You can do this in the _ViewImports.cshtml file, using the `@addTagHelper` directive and specifying the fully qualified name of the Tag Helper and the assembly, as in this example:

```
@addTagHelper CustomTagHelpers.SystemInfoTagHelper, CustomTagHelpers
```

Alternatively, you can add all the Tag Helpers from a given assembly by using the wildcard syntax, `*`, and specifying the assembly name:

```
@addTagHelper *, CustomTagHelpers
```

With your custom Tag Helper created and registered, you're now free to use it in any of your Razor views, partial views, or layouts.

TIP If you're not seeing IntelliSense for your Tag Helper in Visual Studio, and the Tag Helper isn't rendered in the bold font used by Visual Studio, you probably haven't registered your Tag Helpers correctly in _ViewImports .cshtml using `@addTagHelper`.

The `SystemInfoTagHelper` is an example of a Tag Helper that generates content, but you can also use Tag Helpers to control how existing elements are rendered. In the next section you'll create a simple Tag Helper that can control whether an element is rendered based on an HTML attribute.