```
</p>
```

Instead of creating a new element, as you did for `SystemInfoTagHelper` (`<system-info>`), you'll create a Tag Helper that you apply as an attribute to existing HTML elements. This Tag Helper does one thing: controls the visibility of the element it's attached to. If the value passed in the `if` attribute is `true`, the element and its content is rendered as normal. If the value passed is `false`, the Tag Helper removes the element and its content from the template. The following listing shows how you could achieve this.

Listing 32.2 Creating an `IfTagHelper` to conditionally render elements

```
[HtmlTargetElement(Attributes = "if")]                          ❶
public class IfTagHelper : TagHelper
{
    [HtmlAttributeName("if")]                                   ❷
    public bool RenderContent { get; set; } = true;

    public override void Process(                               ❸
        TagHelperContext context, TagHelperOutput output)       ❸
    {
        if(RenderContent == false)                              ❹
        {
            output.TagName = null;                              ❺
            output.SuppressOutput();                            ❻
        }
    }

    public override int Order => int.MinValue;                  ❼
}
```

❶ Setting the Attributes property ensures that the Tag Helper is triggered by an if attribute.

❷ Binds the value of the if attribute to the RenderContent property

❸ The Razor engine calls Process() to execute the Tag Helper.

❹ If the RenderContent property evaluates to false, removes the element

❺ Sets the element the Tag Helper resides on to null, removing it from the page

❻ Doesn't render or evaluate the inner content of the element