Listing 32.4 Implementing a Markdown Tag Helper using Markdig

```
public class MarkdownTagHelper: TagHelper                    ❶
{
    public override async Task ProcessAsync(
        TagHelperContext context, TagHelperOutput output)
    {
        TagHelperContent markdownRazorContent = await        ❷
            output.GetChildContentAsync();                   ❷
        string markdown =                                    ❸
            markdownRazorContent.GetContent();               ❸

        string html = Markdig.Markdown.ToHtml(markdown);     ❹

        output.Content.SetHtmlContent(html);                 ❺
        output.TagName = null;                               ❻
    }
}
```

❶ The Markdown Tag Helper will use the <markdown> element.

❷ Retrieves the contents of the <markdown> element

❸ Renders the Razor contents to a string

❹ Converts the Markdown string to HTML using Markdig

❺ Writes the HTML content to the output

❻ Removes the <markdown> element from the content

When rendered to HTML, the Markdown content in listing 32.3 becomes

```
<h2>This is a markdown title</h2>
<p>This is a markdown list:</p>
<ul>
<li>Item 1</li>
<li>Item 2</li>
</ul>
<div>
  Content is shown when showContent is true
</div>
```

NOTE In listing 32.4 we implemented `ProcessAsync()` instead of `Process()` because we called the `async` method