well as rendering logic (deciding how the panel should be displayed).

TIP Use partial views when you want to encapsulate the rendering of a specific view model or part of a view model. Consider using a view component when you have rendering logic that requires business logic or database access or when the section is logically distinct from the main page content.

You invoke view components directly from Razor views and layouts using a Tag Helper-style syntax with a `vc:` prefix:

```
<vc:my-recipes number-of-recipes="3">
</vc:my-recipes>
```

Custom view components typically derive from the `ViewComponent` base class and implement an `InvokeAsync()` method, as shown in listing 32.5. Deriving from this base class allows access to useful helper methods in much the same way that deriving from the `ControllerBase` class does for API controllers. Unlike with API controllers, the parameters passed to `InvokeAsync` don't come from model binding. Instead, you pass the parameters to the view component using properties on the Tag Helper element in your Razor view.

Listing 32.5 A custom view component to display the current user's recipes

```
public class MyRecipesViewComponent : ViewComponent                ❶
{
    private readonly RecipeService _recipeService;                 ❷
    private readonly UserManager<ApplicationUser> _userManager;    ❷
    public MyRecipesViewComponent(RecipeService recipeService,     ❷
        UserManager<ApplicationUser> userManager)                  ❷
    {                                                              ❷
        _recipeService = recipeService;                            ❷
```