2. Configure the FluentValidation library for MVC and Razor Pages in Program.cs by calling `builder.Services.AddFluentValidationAutoValidation()`. You can further configure the library as shown in listing 32.15.
3. Register your validators (such as the `CurrencyConverterModelValidator` from listing 32.13) with the DI container. These can be registered manually, using any scope you choose:

```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args);
builder.Services.AddRazorPages();
builder.Services.AddFluentValidationAutoValidation();
builder.services.AddScoped<
    IValidator<CurrencyConverterModelValidator>,
    CurrencyConverterModelValidator>();
```

   Alternatively, you can allow FluentValidation to automatically register all your validators using the options shown in listing 32.15.

For such a mature library, FluentValidation has relatively few configuration options to decipher. The following listing shows some of the options available; in particular, it shows how to automatically register all the custom validators in your application and disable `DataAnnotations` validation.

Listing 32.15 Configuring FluentValidation in an ASP.NET Core application

```
var builder = WebApplication.CreateBuilder(args);

builder.Services.AddRazorPages();

builder.Services.AddValidatorsFromAssemblyContaining<Program>();    ❶

builder.Services.AddFluentValidationAutoValidation(                 ❷
```