**Figure 33.5 Using the `PolicyHttpMessageHandler` to handle transient errors. If an error occurs when calling the remote API, the Polly handler will automatically retry the request. If the request then succeeds, the result is passed back to the caller. The caller didn't have to handle the error, making it simpler to use the `HttpClient` while remaining resilient to transient errors.**

To add transient error handling to a named client or `HttpClient`, follow these steps:

1. Install the Microsoft.Extensions.Http.Polly NuGet package in your project by running `dotnet add package Microsoft.Extensions.Http.Polly`, by using the NuGet explorer in Visual Studio, or by adding a `<PackageReference>` element to your project file as follows:

```
<PackageReference Include="Microsoft.Extensions.Http.Polly"
    Version="7.0.0" />
```

2. Configure a named or typed client as shown in listings 33.4 and 33.7.
3. Configure a transient error-handling policy for your client as shown in list- ing 33.8.

**Listing 33.8 Configuring a transient error-handling policy for a typed client**

```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args);
builder.services.AddHttpClient<ExchangeRatesClient>()     ❶
    .AddTransientHttpErrorPolicy(policy =>                ❷
        policy.WaitAndRetryAsync(new[] {                  ❸
            TimeSpan.FromMilliseconds(200),               ❹
            TimeSpan.FromMilliseconds(500),               ❹
```