- *Program.cs*—As in a typical ASP.NET Core application, this contains the entry point for your application, and it's where the `IHost` is built and run. By contrast with a typical .NET 7 ASP.NET Core app, it uses the generic host instead of the minimal hosting `WebApplication` and `WebApplicationBuilder`.

Listing 34.6 Default BackgroundService implementation for worker service template

```
public class Worker : BackgroundService                    ❶
{
    private readonly ILogger<Worker> _logger;
    public Worker(ILogger<Worker> logger)
    {
        _logger = logger;
    }

    protected override async Task ExecuteAsync(            ❷
        CancellationToken stoppingToken)
    {
        while (!stoppingToken.IsCancellationRequested)     ❸
        {
            _logger.LogInformation(
                "Worker running at: {time}", DateTimeOffset.Now);
            await Task.Delay(1000, stoppingToken);         ❹
        }
    }
}
```

❶ The Worker service derives from BackgroundService.

❷ ExecuteAsync starts the main execution loop for the service.

❸ When the app is shutting down, the CancellationToken is canceled.

❹ The service writes a log message every second until the app shuts down.

The most notable difference between the worker service template and an ASP.NET Core template is that Program.cs doesn't use the `WebApplicationBuilder` and `WebApplication` APIs for minimal hosting. Instead, it uses the