```
<Project Sdk="Microsoft.NET.Sdk.Worker">                                  ❶

  <PropertyGroup>
    <TargetFramework>net7.0</TargetFramework>                             ❷
    <Nullable>enable</Nullable>
    <ImplicitUsings>enable</ImplicitUsings>
    <UserSecretsId>5088-4277-B226-DC0A790AB790</UserSecretsId>            ❸
  </PropertyGroup>

  <ItemGroup>
    <PackageReference Include="Microsoft.Extensions.Hosting"              ❹
        Version="7.0.0" />                                                ❹
    <PackageReference Include="Microsoft.Extensions.Http"                 ❺
        Version="7.0.0" />                                                ❺
    <PackageReference Include="Microsoft.EntityFrameworkCore.Design"      ❻
         Version="7.0.0" PrivateAssets="All" />                           ❻
    <PackageReference Include="Microsoft.EntityFrameworkCore.Sqlite"      ❻
         Version="7.0.0" />                                               ❻
  </ItemGroup>
</Project>
```

❶ Worker services use a different project software development kit (SDK) type from ASP.NET Core apps.

❷ The target framework is the same as for ASP.NET Core apps.

❸ Worker services use configuration so they can use User Secrets, like ASP.NET Core apps.

❹ All worker services must explicitly add this package. ASP.NET Core apps add it implicitly.

❺ If you're using IHttpClient-Factory, you'll need to add this package in worker services.

❻ EF Core packages must be explicitly added, the same as for ASP.NET Core apps.

Some parts of the project file are the same for both worker services and ASP.NET Core apps:

- Both types of apps must specify a `<TargetFramework>`, such as `net7.0` for .NET 7.
- Both types of apps use the configuration system, so you can use `<UserSecretsId>` to manage secrets in development, as discussed in chapter 10.