`[InlineData]` isn't the only way to provide the parameters for your theory tests, but it's one of the most commonly used. You can also use a static property on your test class with the `[MemberData]` attribute or a class itself using the `[ClassData]` attribute.

TIP I describe how you can use the `[ClassData]` and `[MemberData]` attributes in my blog post "Creating parameterised tests in xUnit with `[InlineData]`, `[ClassData]`, and `[MemberData]`": http://mng.bz/8ayP.

You now have some tests for the happy path of the `ConvertToGbp()` method, and I even sneaked an edge case into listing 35.5 by testing the case where `value = 0`. The final concept I'll cover is testing error cases, where invalid values are passed to the method under test.

35.6 Testing failure conditions

A key part of unit testing is checking whether the system under test handles edge cases and errors correctly. For the `CurrencyConverter`, that would mean checking how the class handles negative values, small or zero exchange rates, large values and rates, and so on.

Some of these edge cases might be rare but valid cases, whereas other cases might be technically invalid. Calling `ConvertToGbp` with a negative `value` is probably valid; the converted result should be negative too. On the other hand, a negative exchange rate doesn't make sense conceptually, so it should be considered an invalid value.

Depending on the design of the method, it's common to throw exceptions when invalid values are passed to a method. In listing 35.3 you saw that we throw an