The middleware you'll be testing is shown in listing 36.1. When invoked, this middleware checks that the path starts with `/ping` and, if it does, returns a plain text `"pong"` response. If the request doesn't match, it calls the next middleware in the pipeline (the provided `RequestDelegate`).

Listing 36.1 `StatusMiddleware` to be tested, which returns a `"pong"` response

```
public class StatusMiddleware
{
    private readonly RequestDelegate _next;                          ❶
    public StatusMiddleware(RequestDelegate next)                    ❶
    {
        _next = next;
    }
    public async Task Invoke(HttpContext context)                    ❷
    {
        if(context.Request.Path.StartsWithSegments("/ping"))         ❸
        {                                                            ❸
            context.Response.ContentType = "text/plain";             ❸
            await context.Response.WriteAsync("pong");               ❸
            return;                                                  ❸
        }                                                            ❸
        await _next(context);                                        ❹
    }
}
```

❶ The RequestDelegate representing the rest of the middleware pipeline

❷ Called when the middleware is executed

❸ If the path starts with "/ping", a "pong" response is returned . . .

❹ . . . otherwise, the next middleware in the pipeline is invoked.

In this section, you're going to test two simple cases:

- When a request is made with a path of `"/ping"`
- When a request is made with a different path