conditionally, based on the hosting environment. `WebApplication` automatically adds the developer exception page when running in the development hosting environment, so you typically add `ExceptionHandlerMiddleware` when you're *not* in the development environment, as shown in the following listing.

Listing 4.5 Adding exception-handler middleware when in production

```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args);
WebApplication app = builder.Build();                                    ❶

if (!app.Environment.IsDevelopment())                                    ❷
{
    app.UseExceptionHandler("/error");                                   ❸
}

// additional middleware configuration
app.MapGet("/error", () => "Sorry, an error occurred");                  ❹
```

❶ In development, WebApplication automatically adds the developer exception page middleware.

❷ Configures a different pipeline when not running in development

❸ The ExceptionHandlerMiddleware won't leak sensitive details when running in production.

❹ This error endpoint will be executed when an exception is handled.

As well as demonstrating how to add `ExceptionHandlerMiddleware` to your middleware pipeline, this listing shows that it's perfectly acceptable to configure different middleware pipelines depending on the environment when the application starts. You could also vary your pipeline based on other values, such as settings loaded from configuration.

NOTE You'll see how to use configuration values to customize the middleware pipeline in chapter 10.

When adding `ExceptionHandlerMiddleware` to your application, you typically provide a path to the custom error page that will be