CRUD (Create, Read, Update, Delete) API using different HTTP verbs, as discussed in section 5.2.1.

Listing 5.2 Creating route handlers for a simple CRUD API

```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args);
WebApplication app = builder.Build();

app.MapGet("/fruit", () => Fruit.All);                          ❶

var getFruit = (string id) => Fruit.All[id];                    ❷
app.MapGet("/fruit/{id}", getFruit);                            ❷

app.MapPost("/fruit/{id}", Handlers.AddFruit);                  ❸

Handlers handlers = new();                                      ❹
app.MapPut("/fruit/{id}", handlers.ReplaceFruit);               ❹

app.MapDelete("/fruit/{id}", DeleteFruit);                      ❺

app.Run();

void DeleteFruit(string id)                                     ❺
{
    Fruit.All.Remove(id);
}

record Fruit(string Name, int Stock)
{
    public static readonly Dictionary<string, Fruit> All = new();
};

class Handlers
{
    public void ReplaceFruit(string id, Fruit fruit)            ❻
    {
        Fruit.All[id] = fruit;
    }

    public static void AddFruit(string id, Fruit fruit)         ❼
    {
        Fruit.All.Add(id, fruit);
    }
}
```

❶ Lambda expressions are the simplest but least descriptive way to create a handler.