The final segment of figure 6.6, `{id?}`, defines an optional route parameter called `id`. This segment of the URL is optional. If this segment is present, the router captures the value for the `{id}` parameter; if the segment isn't there, the router doesn't create a route value for `id`.

You can specify any number of route parameters in your templates, and these values will be available to you for model binding. The complex route template shown in figure 6.6 allows you to match a greater variety of URLs by making `{name}` and `{id}` optional and by providing a default for `{name}`. Table 6.1 shows some of the URLs that this template would match and the corresponding route values that the router would set.

Table 6.1 URLs that would match the template of figure 6.7 and their corresponding route values

URL	Route values
/product/shoes/formal/3	category=shoes, name=formal, id=3
/product/shoes/formal	category=shoes, name=formal
/product/shoes	category=shoes, name=all
/product/bags/satchels	category=bags, name=satchels
/product/phones	category=phones, name=all
/product/computers/laptops/ABC-123	category=computers, name=laptops, id=ABC-123

Note that there's no way to specify a value for the optional `{id}` parameter without also specifying the `{category}` and `{name}` parameters. You can put an optional parameter (that doesn't have a default) only at the end of a route template.

Using default values allows you to have multiple ways to call the same URL, which may be desirable in some cases. Given the route template in figure