❹ Creates a link using the route name “product” and provides a value for the route parameter

❺ Returns the value “View the product at /product/big-widget”

The `WithName()` method adds metadata to your endpoints so that they can be referenced by other parts of your application. In this case, we’re adding a name to the endpoint so we can refer to it later. You’ll learn more about metadata in chapter 11.

NOTE Endpoint names are case-sensitive (unlike the route templates themselves) and must be globally unique. Duplicate names cause exceptions at runtime.

The `LinkGenerator` is a service available anywhere in ASP.NET Core. You can access it from your endpoints by including it as a parameter in the handler.

NOTE You can reference the `LinkGenerator` in your handler because it’s registered with the dependency injection container automatically. You’ll learn about dependency injection in chapters 8 and 9.

The `GetPathByName()` method takes the name of a route and, optionally, route data. The route data is packaged as key-value pairs into a single C# anonymous object. If you need to pass more than one route value, you can add more properties to the anonymous object. Then the helper will generate a path based on the referenced endpoint’s route template.

Listing 6.2 shows how to generate a path. But you can also generate a complete URL by using the `GetUriByName()` method and providing values for the host and scheme, as in this example:

```
links.GetUriByName("product", new { Name = "super-fancy-widget"},
    "https", new HostString("localhost"));
```