- `[FromQuery]`—As you've already seen, this attribute forces a parameter to bind to the query string.
- `[FromRoute]`—This attribute forces the parameter to bind a route parameter value. Note that if a parameter of the required name doesn't exist in the route template, you'll get an exception at runtime.
- `[FromHeader]`—This attribute binds a parameter to a header value in the request.

### Listing 7.1 Binding simple values using `[From]` attributes

```
using Microsoft.AspNetCore.Mvc;                                    ❶

WebApplicationBuilder builder = WebApplication.CreateBuilder(args);
WebApplication app = builder.Build();

app.MapGet("/products/{id}/paged",
    ([FromRoute] int id,                                           ❷
     [FromQuery] int page,                                         ❸
     [FromHeader(Name = "PageSize")] int pageSize)                 ❹
     => $"Received id {id}, page {page}, pageSize {pageSize}");

app.Run();
```

❶ All the [From*] attributes are in this namespace.

❷ [FromRoute] forces the argument to bind to the route value.

❸ [FromQuery] forces the argument to bind to the query string.

❹ [FromHeader] binds the argument to the specified header.

Later, you'll see other attributes, such as `[FromBody]` and `[FromServices]`, but the preceding three attributes are the only `[From*]` attributes that operate on simple types such as `int` and `double`. I prefer to avoid using `[FromQuery]` and `[FromRoute]` wherever possible and rely on the default binding conventions instead, as I